

AMF 19+



GO Touchless[📶]

Use With Full Capacity



Palm Capacity
1,000

Face Capacity
3,000

Password Capacity
3,000

Record Capacity
200,000



Face




Personal
Identity Number



Palm Scanner



Access
Control



USB Disk



Excel Output

Specifications

Hardware Features

| | |
|--------|---|
| Camera | Color + infrared dual camera binocular 300,000 pixels |
|--------|---|

| | |
|----------------|-------------|
| Infrared Light | In the tank |
|----------------|-------------|

| | |
|---------|-------------|
| Display | 1.77 Inches |
|---------|-------------|

| | |
|----------|-------------------|
| Keyboard | Push button input |
|----------|-------------------|

| | |
|--------|-------|
| Memory | 64 MB |
|--------|-------|

| | |
|---------|--------|
| Storage | 128 MB |
|---------|--------|

| | |
|-------------------------|-------------|
| Communication interface | Flash drive |
|-------------------------|-------------|

| | |
|-----------------------|----------|
| False acceptance rate | <0.0001% |
|-----------------------|----------|

| | |
|---------------------------|-----|
| USB flash drive interface | Yes |
|---------------------------|-----|

| | |
|---------------|-----|
| Speech Output | Yes |
|---------------|-----|

| | |
|-----------|----------|
| Clock RTC | Exterior |
|-----------|----------|

| | |
|-------------------|-------|
| Operating Voltage | DC 5V |
|-------------------|-------|

| | |
|--------------|----------|
| Rated inputs | DC 5V 2A |
|--------------|----------|

| | |
|---------------|------------|
| Ambient Light | 0-8000 Lux |
|---------------|------------|

| | |
|-----------------------|------------|
| Operating Temperature | 0°C - 45°C |
|-----------------------|------------|

| | |
|--------------------|-------------------------|
| Operating Humidity | 0% - 80% non-condensing |
|--------------------|-------------------------|

| | |
|--------------------|------------------|
| Product dimensions | 86mm*86mm*23.5mm |
|--------------------|------------------|

| | |
|--------------|-----------------|
| Package size | 115mm*90mm*30mm |
|--------------|-----------------|

| | |
|------------|------|
| Net weight | 106g |
|------------|------|

| | |
|--------------|------|
| Gross weight | 140g |
|--------------|------|

Software Features

| | |
|---------------|------|
| User capacity | 3000 |
|---------------|------|

| | |
|---------------|------|
| Face capacity | 3000 |
|---------------|------|

| | |
|---------------|------|
| Palm capacity | 1000 |
|---------------|------|

| | |
|-------------------|------|
| Password capacity | 3000 |
|-------------------|------|

Specifications

| | |
|---------------------------------|-------------------------------------|
| Record capacity | 200,000 |
| Department | 16 |
| Shift | 24 |
| Bell | 24 |
| Verification method | Face, Palm, Vein, QR Code, Password |
| How to confirm | FC/PP/P/2D , P+FC/PP/2D |
| Supported languages | Chinese simplified, English |
| Export report languages | Chinese simplified, English |
| Self-test function | Manual detection |
| Power management features | Screensaver feature |
| Face verification speed | < 0.6s |
| Face FAR/FRR | 0.0001 / 0.1% |
| Face recognition mode | 1:N |
| Palmar vein verifies speed | < 0.6s |
| Palmar vein FAR/FRR | 0.00001 / 0.1% |
| Palmar vein recognition pattern | 1:N |



Face




Personal
Identity Number



Palm Scanner



Access
Control



USB Disk



Excel Output